

LINAIRE® Flex Tube 360

Linear Light

Round, flexible architectural light that bends and emits light in all directions. Water resistant with precision light quality and full diffusion for a dotless look.

Date \_\_\_\_\_

Project Notes \_\_\_\_\_



FEATURES	HYBRID ORDERING CODE (OPTIONAL)
<ul style="list-style-type: none"> <li>Bends in all directions for maximum versatility</li> <li>Flexible, durable fixture with no visible dots</li> <li>Water resistant for indoor and outdoor use</li> <li>Emits light in all directions</li> <li>90+ CRI</li> <li>Factory assembly (IP67)</li> <li>Field cuttable, free-cut termination (IP65)</li> </ul>	

ORDERING CODES	HYBRID ORDERING CODE (OPTIONAL)
----------------	---------------------------------


Order spools, and components for field assembly							Soldered Wire Lead and Connection Options					
DI	Voltage	Model	Series	CCT	Length	Wire Entry	Input Wire Color, Length, and Connection			Output Wire Color, Length, and Connection		
	24V (24V Volt)	360	LIN	24 (2400K) 27 (2700K) 30 (3000K) 35 (3500K) 40 (4000K)	016 (16 feet wet location) CSTM_ (__in.) wet location	STE (Straight Wire Entry)	<b>Color &amp; Type</b>	<b>Length</b>	<b>Connection</b>	<b>Color &amp; Type</b>	<b>Length</b>	<b>Connection</b>
							<i>WH</i> (White CL2 - Default)	<i>36l</i> (36 in. - Default)	<i>BW</i> (Bare Wire - Default)	<b>*blank*</b> (No Wire - Default)		
							BL (Black CL2)	__ in.	DC (Barrel)	WH (White CL2)	__ in.	BW (Bare Wire - Default)
									BL (Black CL2)			DC (Barrel)

GENERAL SPECIFICATIONS (ALL MODELS)


<b>Voltage</b>	24VDC
<b>Wattage</b>	3.7W/ft.
<b>2400K</b>	239 Lm/ft.
<b>2700K</b>	247 Lm/ft.
<b>3000K</b>	250 Lm/ft.
<b>3500K</b>	254 Lm/ft.
<b>4000K</b>	260 Lm/ft.
<b>Cut Points</b>	Free Cut (cut anywhere)
<b>Dimmable</b>	Yes
<b>Max Run (ft.)</b>	16.4 ft.
<b>CRI</b>	90+
<b>Dimensions</b>	0.71 x 0.71 in. (W x H)
<b>TM-21 (LM-80)</b>	>50,000 hours
<b>Environment</b>	Outdoor / Wet Location (IP65 / IP67)
<b>Lead Wire A</b>	96 in. White Bare Lead 18/2 AWG UL 2464 Wire with Strain Relief
<b>Lead Wire B</b>	96 in. White Bare Lead 18/2 AWG UL 2464 Wire with Strain Relief
<b>LED Chips</b>	146/ft.
<b>Chip Type</b>	2835
<b>Certification</b>	UL Listed 2108
<b>Limited Warranty</b>	5 Year Limited Warranty

**MECHANICAL DIAGRAMS**

**24V-360-LIN**




**CONNECTIONS**



**ACCESSORIES**


**DI-LIN-360-MTCL-2**

LINAIRE Flex, Tube 360, Mounting Clip, 2 Pack




**DI-LIN-360-MTBR-2**

LINAIRE Flex, Tube 360, Mounting Bracket, 2 Pack




**DI-LIN-360-HNG-2**

LINAIRE Flex, Tube 360, Hanging Hardware, 2 Pack



**DI-LIN-360-FEC**

LINAIRE Flex, Tube 360 End Cap, 2 Pack



**DELIVERY OPTIONS**

- **Factory + Field (Hybrid) (IP65)**  
Fastest order fulfillment. Field connectors and accessories not included.
- **Factory Assembly (IP67)**  
Onsite modifications with factory connection. Additional accessories not included.

**RECOMMENDED POWER SUPPLIES**

For additional Power Supply information, refer to individual Specification Sheet data at diodeled.com.

- OMNIDRIVE X
- VLM
- MAGNETIC DIMMABLE DRIVER
- 0-10V
- LUTRON
- MEANWELL
- OMNIDRIVE
- OMNIDRIVE BASICS
- SWITCHEX

**OMNIDRIVE® X DIMMABLE DRIVER**

For additional information visit:  
<https://lucettaci.com/products/omnidrive-x>

Versatile driver for most high-performance dimming on ELV, TRIAC, and 0-10V systems.

SKU	GENERAL SPECS	INPUT VOLTAGE / FREQUENCY	OUTPUT VOLTAGE & MAXIMUM LOAD	MINIMUM LOAD
DI-ODX-24V120W-J	Dimmable 8.66 x 3.7 x 1.57 in.	120-277VAC, 50/60Hz	24V / 120W	None
DI-ODX-24V200W-J	Dimmable 10.24 x 4.13 x 1.77 in.	120-277VAC, 50/60Hz	24V / 200W	None
DI-ODX-24V30W	Class 2, Dimmable 6.1 x 2.1 x 0.8 in.	120-277VAC, 50/60Hz	24V / 30W	None
DI-ODX-24V30W-J	Class 2, Dimmable 6.5 x 3.7 x 1.57 in.	120-277VAC, 50/60Hz	24V / 30W	None
DI-ODX-24V60W	Class 2, Dimmable 7 x 2.4 x 1 in.	120-277VAC, 50/60Hz	24V / 60W	None
DI-ODX-24V60W-J	Class 2, Dimmable 7.4 x 3.7 x 1.57 in.	120-277VAC, 50/60Hz	24V / 60W	None
DI-ODX-24V96W	Class 2, Dimmable 9 x 2.7 x 1.7 in.	120-277VAC, 50/60Hz	24V / 96W	None
DI-ODX-24V96W-J	Class 2, Dimmable 8.66 x 3.7 x 1.57 in.	120-277VAC, 50/60Hz	24V / 96W	None
DI-AWNAUX-ODX-24V96W-LPS3R	Class 2, Dimmable 10.79 x 7.34 x 2.36 in.	120-277V	24V / 96W	None
DI-AWNAUX-ODX-24V60W-LPS3R	Class 2, Dimmable 10.79 x 7.34 x 2.36 in.	120-277V	24V / 60W	None
DI-AWNAUX-ODX-24V30W-LPS3R	Class 2, Dimmable 10.79 x 7.34 x 2.36 in.	120-277V	24V / 30W	None
DI-AWN-ODX-24V96W-J	Class 2, Dimmable 8.66 x 3.7 x 1.57 in.	120-277V	24V / 96W	None
DI-AWN-ODX-24V60W-J	Class 2, Dimmable 7.4 x 3.7 x 1.57 in.	120-277V	24V / 60W	None
DI-AWN-ODX-24V30W-J	Class 2, Dimmable 6.5 x 3.7 x 1.57 in.	120-277V	24V / 30W	None

**VLM SERIES CONSTANT VOLTAGE DRIVER**

Compact driver for on/off, PWM dimming, and color-changing applications.

SKU	GENERAL SPECS	INPUT VOLTAGE / FREQUENCY	OUTPUT VOLTAGE & MAXIMUM LOAD	MINIMUM LOAD
VLM100W-24	Class 2 5.38 x 1 x 0.77 in.	120 / 277VAC 47 - 63Hz	24V / 96W	None
VLM100W-24-LPM	Class 2 8.19 x 2.94 x 1.31 in.	120 / 277VAC 47 - 63Hz	24V / 96W	None
VLM100W-24-LPS	Class 2 11.25 x 3.75 x 1.9 in.	120 / 277VAC 47 - 63Hz	24V / 96W	None
VLM100W-24-LPS3R	Class 2 10.79 x 7.34 x 2.36 in.	120 / 277VAC 47 - 63Hz	24V / 96W	None
VLM200W-24-LPL	Class 2 13.5 x 4.5 x 2.38 in.	120 / 277VAC 47 - 63Hz	24V / 100W (X2)	None
VLM60W-24	Class 2 5.1 x 0.75 x 0.77 in.	120 / 277VAC 47 - 63Hz	24V / 60W	None
VLM60W-24-LPM	Class 2 8.19 x 2.94 x 1.31 in.	120 / 277VAC 47 - 63Hz	24V / 60W	None
VLM60W-24-LPS	Class 2 11.25 x 3.75 x 1.9 in.	120 / 277VAC 47 - 63Hz	24V / 60W	None
VLM60W-24-LPS3R	Class 2 10.79 x 7.34 x 2.36 in.	120 / 277VAC 47 - 63Hz	24V / 60W	None

**RECOMMENDED CONTROLLERS**

For additional Controller information, refer to individual Specification Sheet data at diodeled.com.

**CASAMBI® CONTROLLERS**

The CASAMBI controllers will remotely control your lighting through the app - downloadable for IOS & Android.

SKU	DESCRIPTION
<b>CBU-A2D</b>	CASAMBI A2D 2 Channel 0-10V/DALI Controller
<b>CBU-ASR</b>	CASAMBI ASR 0-10V Controller
<b>CBU-PWM4</b>	CASAMBI PWM4 Single Color Dimming Controller
<b>DI-CBU-PWM5-PRO</b>	Casambi CBU-PWM5-Pro RGB/W/WW Applications, 5 x PWM for constant voltage lights, 4 amps/CH max

**TOUCHDIAL™ CONTROL SYSTEMS**

The TOUCHDIAL™ zone control system controls single color dimming, tunable white, and color changing LED lighting via mobile device and additional TOUCHDIAL controls.

SKU	DESCRIPTION
<b>DI-RF-REC-CV-A</b>	TOUCHDIAL Color Control System - WiFi Receiver
<b>DI-RF-REC-CV-SC</b>	TOUCHDIAL Mini Receiver - Single Channel and Zone
<b>DI-RF-REM-DIM-1</b>	TOUCHDIAL Mini Remote - Single Zone
<b>DI-RF-REM-DIM-5</b>	TOUCHDIAL Remote Dimmer 5-Zone Dimmer Control
<b>DI-RF-REM-RGBW-1</b>	TOUCHDIAL Mini Remote RGB(W) - Single Zone
<b>DI-RF-REM-RGBW-4</b>	TOUCHDIAL Color Control System - RGB/RGBW 4-Zone Remote Controller
<b>DI-RF-REM-TW-4</b>	TOUCHDIAL Color Control System - Tunable White 4-Zone Remote Controller
<b>DI-RF-WMT-DIM</b>	TOUCHDIAL Wall Dimmer - Single Zone
<b>DI-RF-WMT-RGBW</b>	TOUCHDIAL RGB(W) Wall Control - Single Zone
<b>DI-RF-WPD-DIM-1</b>	TOUCHDIAL Paddle Dimmer - Single Zone
<b>DI-RF-WPD-DIM-2</b>	TOUCHDIAL Paddle Dimmer - Two Zone
<b>DI-WIFI-RF-TRMS</b>	TOUCHDIAL Color Control System - WiFi Hub
<b>DI-RF-REM-TW3-4</b>	TOUCHDIAL Color Control System, 3-Anchor Tunable White 4-Zone Remote Controller

## CERTIFICATIONS

### Safety

- UL Listed 2108 Low Voltage Lighting System / Low Voltage Luminaire. UL 1598 / CSA 250.0-08, UL 8750. UL 879 / CAN/CSA-C22.2 no. 207-M89. Certified for United States and Canada. File # E469769.
- UL Listed Field Cuttable.
- Approved for storage areas of clothes closets per NEC 410.16.A.1,3 and 410.16.C.1,3,5

### Environment

- IP65 - Field Connections and Terminations
- IP67 - Stock Spools and Factory Assembled Fixtures
- Ambient Temperature: -4 ~ 122°F (-20 ~ 50°C)
- Operating Temperature: -4 ~ 176°F (-20 ~ 80°C)

### Performance

- DI-24V-TE-LIN3: Can be used to comply with TITLE 24 Part 6 High Efficacy Lighting LED requirements - JA8-2016-2022-E
- LED chip data measured in accordance to IES LM-80-08.
- Photometric & Colorimetry data measured in accordance to IES LM-79-08, in Elemental LED's Innovation Lab.

### Safety / Warnings / Disclosures

1. Install in accordance with national and local electrical code regulations.
2. This product is intended to be installed and serviced by a qualified, licensed electrician.
3. Only use copper wiring. Use wires rated for at least 176°F (80°C) and certified for use with external connection of electrical equipment.
4. Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length.
5. Tape light, attached wire leads, and additional extension cables, connectors, etc., are not rated for in-wall installation unless otherwise noted. Tape light and attached wire leads are field-cuttable.
6. Ensure applicable wire is installed between driver, fixture, and any controls in-between. When choosing wire, factor in voltage drop, amperage rating, and type (in-wall rated, wet location rated, etc.). Inadequate wire installation could overheat wires, and cause fire.
7. Do not install in environment where excessive heat may exist (ex. close proximity to fireplace, etc.) See Ambient Temperature ratings
8. Do not install indoor LED tape light products in outdoor / wet location environments. Only wet location tape light models are rated for outdoor / wet locations.
9. Do not modify product beyond instructions or warranty will be void.
10. Tape light must be handled with care. Excessive handling, bending, and pressure may damage the product, voiding the warranty.
11. Actual color may vary from what is pictured on this sheet and other print materials due to the limitations of photographic processes.
12. We reserve the right to modify and improve the design of our fixtures without prior notice. We cannot guarantee to match existing installed fixtures for subsequent orders or replacements in regards to product appearance, CCT, or lumen output.

## LIMITED WARRANTY

- 5 Year Limited Warranty

This warranty does not include the additional accessories referenced in this specification sheet. Complete warranty details for fixtures and additional accessories are available at [www.dioleed.com/limited-warranty/](http://www.dioleed.com/limited-warranty/) within the Policies section. For warranty related questions please contact product support.

### Consumer's Acknowledgment

Elemental LED, Inc. stands behind its products when they are used properly and according to our specifications. By purchasing our products, the purchaser agrees and acknowledges that lighting design, configuration and installation is a complex process, wherein seemingly minor factors or changes in layout and infield adjustments can have a significant impact on an entire system. Choosing the correct components is essential. Elemental LED is able to work with the original purchaser to make an appropriate product selection to the extent of the limited information that the customer can provide, but it is virtually impossible for Elemental LED to design a system that foresees every unknown factor. For this reason, this Warranty does not cover problems caused by improper design, configuration or installation issues. Any statement from a Elemental LED employee or agent regarding a customer's bill of goods and/or purchase order is NOT an acknowledgment that the products purchased are designed and configured correctly. The purchase agrees and acknowledges that it is the customer's responsibility to adhere strictly to all information contained in the Product Specification Sheets.

There is often more than one way to design, configure and layout an LED lighting application properly to achieve the same lighting effect. Elemental LED strongly recommends that licensed professionals be used in the design and installation of lighting systems that include Elemental LED products. The specifications include important information that a designer and installer should carefully review and strictly follow. Qualified designers and certified and/or licensed installers, with access to the final installation environment, customer goals, and Elemental LED product specifications can make the requisite decisions appropriate for a successful finished lighting application.

- Lumen value measured in accordance to IES LM-79-08. LED chips have a luminous flux range with a tolerance of +/- 5%.
- Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length. Max run may exceed Class 2 limit. Actual wattage may differ from calculated wattage due to voltage drop across run.
- Do not install product in an environment outside the listed ambient temperature. Exceeding the maximum ambient temperature may damage LED chips, reduce the total lamp life, lumen output, and/or adversely impact color consistency.
- Actual efficacy value is dependent to specified LED driver (power supply). An estimated efficacy value can be calculated as follows: Lumen value divided by average power consumption per foot.
- Operating temperature is measured according to the minimum and maximum ambient temperature environment.